

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 07-244980
(43)Date of publication of application : 19.09.1995

(51)Int.Cl. G11C 11/401
G01R 31/28
G11C 11/406
G11C 29/00


(21)Application number : 06-030663 (71)Applicant : NEC CORP
(22)Date of filing : 28.02.1994 (72)Inventor : UCHIDA KATSUNORI

(54) DYNAMIC MEMORY

(57)Abstract:

PURPOSE: To prevent the loss of storage data at the time of executing an internal test mode by supplying a data shifting clock as a refresh requesting signal to an internal circuit at the time of the internal test mode.

CONSTITUTION: When an internal test mode signal ITM is in the normal operation mode of an inactive level, a data shifting control signal SCN is also in the inactive level and a selector 4 selects a refresh requesting signal TRQ outputted by a refresh timer 2 to transfer it as a refresh requesting signal RPQ to an internal circuit 1. When the signal ITM is in the internal test mode of an active level, the selector 4 selects a data shifting clock SCK in accordance with the active level of the signal SCN to transfer it as a signal RRQ to the circuit 1. By such a constitution, the storage data in the circuit 1 are made not to be lost even when the number of signal terminals is increased and a long time is required for data shiftings.



LEGAL STATUS

[Date of request for examination] 27.10.1995

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number] 2830730

[Date of registration] 25.09.1998

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal]

[rejection]

[Date of extinction of right]